



Bulletin 194R
Fused and Non-Fused Disconnects
 Accessories





Auxiliary Contact Blocks△

	Description	Contact Material	For Use With	Pkg. Quantity	Cat. No.
 Cat. No. 800F-X10	Contact Block Note: Sold only in multiples of 10. Order (quantity of) 10 to receive one package of 10 pieces. Latch not included.	N.O.	194R 30/60 A switches (all) 194R 100...1250 A switches (fused only)	10	800F-X10
		N.C.			800F-X01
		N.O.E.M.			800F-X10E
		N.C.L.B.			800F-X01L
		N.O. with stab terminals			800F-X10T
		N.C. with stab terminals			800F-X01T
		N.O. spring-clamp			800F-Q10
		N.C. spring-clamp			800F-Q01
	Auxiliary contact N.O./N.C.		194R 100...1250 A switches (non-fused only)§	1	194R-1STNONC
				1	194R-2NDNONC

△ Also used for test mode function for 20...63 A switches.

§ Does not carry UL Certification

Operating Handles (Accepts 3 Padlocks)

	Description	For Use With	Color	Degree of Protection	Cat. No.
 	Padlockable handle, standard	Bul. 194R disconnect switches up to 60 A	Black	Type 3R, 3, 12, 4, 4X	194R-PB
			Red/Yellow	Type 3R, 3, 12, 4, 4X	194R-PY
	Padlockable handle, test mode	Bul. 194R disconnect switches up to 60 A	Black	Type 3R, 3, 12, 4, 4X	194R-PBT
			Red/Yellow	Type 3R, 3, 12, 4, 4X	194R-PYT
	Operating Handle Standard orientation with defeater	IEC Non-fused disconnect switches: 125...630 A IEC Fused disconnect switches: 100...400 A UL Disconnect switches: 100...400 A	Black	IP66 (Type 1, 3R, 12, 4, 4X)	194R-HM4
			Red/Yellow	IP66 (Type 1, 3R, 12, 4, 4X)	194R-HM4E
		IEC Non-fused disconnect switches: 800...1250 A IEC Fused disconnect switches: 630...1250 A UL Non-fused disconnect switches: 600...1200 A UL Fused disconnect switches: 600...800 A	Black with light grey cover	IP65 (Type 1, 3R, 12, 4, 4X)	194R-HM4-L
			Red/Yellow	IP65 (Type 1, 3R, 12, 4, 4X)	194R-HM4E-L
	Operating Handle Standard orientation without defeater	IEC Non-fused disconnect switches: 800...1250 A IEC Fused disconnect switches: 630...1250 A UL Non-fused disconnect switches: 600...1200 A UL Fused disconnect switches: 600...800 A	Black with light grey cover	IP65 (Type 1, 3R, 12, 4, 4X)	194R-HM4-N2-L
			Red/Yellow	IP65 (Type 1, 3R, 12, 4, 4X)	194R-HM4E-N2-L