
# **Gas and Air Cocks**

### **Model PB80**

#### **Description**

These gas and air cocks are designed with the following features:

- Large ports to minimize pressure drop and turbulence.
- Teflon seats, stern packing seal, and thrust washer to assure long life.
- Bottom loaded, pressure-retaining stem of rugged construction.
- Adjustable stern gland screw for added wear.
- Self-cleaning chrome-plated brass ball for erosion resistance and durability.
- Fast, quarter-turn operation.
- Non-heat vinyl grip on cadmium plated steel handle.
- Can be installed with flow in either direction.



Dimensions						
DP No.	Size	Port	Α	В	C	
111701	1/4"	0.3149	1.6929	1.1023	1.6535	
111702	3/8"	0.3937	1.9409	1.2913	3.0708	
111703	1/2"	0.5905	2.3503	1.4212	3.0708	
111704	3/4"	0.7874	2.6850	1.8661	3.7795	
111705	1″	0.9842	3.2047	2.0236	3.7795	
111706	1-1/4"	1.2598	3.7401	2.2204	3.7795	
111707	1-1/2"	1.5748	4.0905	2.7795	5.4330	
111708	2"	1.9685	4.9566	3.0748	5.4330	
	•					

#### **Materials Specification**

Item	Name	Material
1	Handle Nut	Cadmium Plated Steel
2	Handle (Vinyl Insulated)	Cadmium Plated Steel
3	Packing Gland	Brass
4	Stem Packing	P.T.F.E.*
5	Thrust Washer	P.T.F.E.*
6	Stem O-Ring	Nitrile Rubber
7	Stem	Hard Chromium Plated Brass
8	Ball	Hard Chromium Plated Brass
9	Seats	P.T.F.E.*
10	Body	Forged Brass
11	End Adapter	Forged Brass

P.T.F.E.\* is Polytetraflouroethylene (Teflon)

#### **Approvals**



(1/2" & 1/4" sizes) 1/2" & 3/4" Tested to ANSI/ASME B16.33





Conforms to Fed. Spec WW-V-35B



# **Gas and Air Cocks**


#### AC929A2

## **Model PGB1020**

#### **Description**

- Compact design for ease of installation.
- Smooth, fast quarter-turn operation.
- Corrosion resistant chrome-plated ball is self-cleaning.
- Forged construction.





#### **Dimensions**

DP No.	Α	В	C	D
111715	1/2"	2.364	1.277	1.411
111716	3/4"	2.60	1.422	1.379

#### **Materials Specification**

al
num
num
nor Bronze
Rubber to ASTM D471
ressed Fiber
Chromium Plated ForgedBrass
Rubber to ASTM D471
l Brass

#### **Approvals**



