

# **Pneumatic Tools**



## 9041 Tyre inflator

#### • Special rubber housing protects manometer against light impacts



- Handle with operating lever and discharge knob (for one-hand use)
- Tube with plug-in nipple
- · Max. pressure: 8 bar
- · Handle with integrated suspension hook
- Measuring range (manometer): 0 12 bar Graduation: 0.1 bar
- Flexible tube, length: 400 mm
- Manometer diameter: 63 mm
- Air connection inlet: inside thread (IG) 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Working pressure (bar): 6.3



| 9000-010 |  |
|----------|--|
|          |  |

| HAZET<br>No. | <b>∆</b> <sup>1</sup> <b>∆</b> | EAN-No.<br>4000896+ |
|--------------|--------------------------------|---------------------|
| 9041-1       | 411                            | 147076              |
|              |                                |                     |

### 9041 Tyre inflator, calibrated





- Handle with operating lever for filling and deflating (for one-hand operation)
- $\bullet$  Hose with plug-in nipple, pivoting through 360°
- Measuring range (manometer) (calibrated): 0-10 bar
- Scale graduation: 0.1 bar
- Flexible hose
- Manometer housing: 63 mm  $\varnothing$
- Length: 685 mm (with coupling)
- Air connection inlet: inside thread (IG) 12.91 mm (¼")
- Coupler plug: Nominal size 7.2 (included)
- Temperature range: -10°C 40°C





| HAZET<br>No. | <b>4</b> 4 | EAN-No.<br>4000896+ |
|--------------|------------|---------------------|
| 9041-2       | 565        | 161928              |

## 9041 Tyre inflator, calibrated

With calibration certificate
 Special rubber housing protects manometer against light impacts




- · Calibration certificate according to German calibration regulations
- Measuring range (manometer) (calibrated): 0-10 bar
- Handle with operating lever for filling and deflating (for one-hand operation)
- Hose with plug-in nipple, pivoting through 360°
- · Scale graduation: 0.1 bar
- Flexible hose
- · Manometer housing diameter: 63 mm
- Length: 685 mm (with coupling)
- Air connection inlet: inside
- thread (IG) 12.91 mm (1/4")

  Coupler plug: Nominal
- Coupler plug: Nominal size 7.2 (included)
- Temperature range:  $-10^{\circ}C 40^{\circ}C$










| HAZET<br>No. | <b>4</b> 4 | EAN-No.<br>400896+ |
|--------------|------------|--------------------|
| 9041-2 CERT  | 565        | 167760             |

## 9041 Tyre inflator

• Extra long hose for better accessibility of the valve



- Application: Particularly suitable for bicycles
- Handle with operating lever for filling and deflating (for one-hand operation)
- Hose with plug-in nipple
- Measuring range (manometer): 0–10 bar
- Scale graduation: 0.1 bar
- Flexible hose
- Manometer housing: 63 mm  $\varnothing$
- Hose length: 1000 mm
- Air connection inlet: inside thread (IG) 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Temperature range: -10°C 40°C





| l | HAZET<br>No. | EAN-No.<br>4000896+ |
|---|--------------|---------------------|
| ı | 9041-3       | 206858              |