

BDF Cling-Lube

DESCRIPCIÓN DEL PRODUCTO:

JAX BDF Cling-Lube fue formulado y probado en conjunto con los departamentos de mantenimiento en las plantas de procesamiento de carne de res reconocidos a nivel nacional que requieren lubricantes de grado alimenticio para aplicaciones generales en las que se requiere adhesión y no goteo sobre el producto. Con su fórmula de espuma y características extremas "adherentes", JAX BDF Cling-Lube se diseñó con los aditivos de extrema presión y anti-desgaste, y superó las expectativas!

JAX BDF Cling-Lube es el lubricante de superior calidad a utilizar en aplicaciones generales en la industria alimenticia.

APLICACIONES:

Una lista parcial de las aplicaciones JAX BDF Cling-Lube incluye:

- Cadenas y bandas transportadoras elevadas
- Carros y guías elevadas
- Transportadores que van dentro o fuera de zonas de alta humedad o zonas de vapor
- Lugares que son difíciles de alcanzar o dónde frecuentemente la lubricación es difícil

DATOS TÉCNICOS:

Propelente:	Propano y Butano
Punto de Inflamación:	352 ° F (178 ° C) concentrado, típico de -94 ° F (-70 ° C) propelente
Patron de rocío:	Espuma típica
Textura:	Película gruesa pegajosa
Apariencia:	Amarillo Claro
Consistencia:	Pesado

AEROSOL EMPAQUE:

Lata de aerosol con peso neto de 11oz (caja x 12 unidades) - # de Parte JAX 214





NSF International / Nonfood Compounds Registration Program

Nonfood Compounds
Program Listed

June 30, 2014

Ms. Patty Riek
Pressure-Lube, Inc. Jax
W134 N5373 Campbell Drive
Menomonee Falls, WI 53051
United States

RE: JAX BDF CLING-LUBE (AEROSOL)
Category Code: H1
NSF Registration No. 127730

Dear Ms. Patty Riek:

NSF has processed the application for Registration of **JAX BDF CLING-LUBE (AEROSOL)** to the NSF International Registration Guidelines for Proprietary Substances and Nonfood Compounds (2009), which are available at www.nsfwhitebook.org. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling review.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the Registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (www.nsfwhitebook.org).

NSF Listing of all Registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF website, at www.nsfwhitebook.org. Changes in formulation or label, without the prior written consent of NSF, will void Registration, and will supersede the on-line listing.

Sincerely,

Amanda Phelka
NSF Nonfood Compounds Registration Program

Company No: N05625

Distributed By:

PRESSURE-LUBE
America's Finest Lubricants