

MIT2500

CAT IV Insulation Testers



- **Insulation testing up to 2.5 kV (New) and 200 GΩ range in a handheld instrument**
- **Guard terminal for high resistance accuracy (New)**
- **Adjustable insulation test voltage from 50 V to 2500 V (New)**
- **Rechargeable options for ac and car charging (New)**
- **Stabilized insulation test voltage (New)**
- **Rechargeable options for ac and car charging (New)**
- **Single range, faster continuity testing from 0.01 Ω to 1 MΩ (New)**
- **Polarization Index (PI) & Dielectric Absorption Ratio (DAR)**
- **CATIV 600V applications**

DESCRIPTION

The MIT2500 insulation and continuity tester has been designed for Electrical and Industrial test applications, where operation voltages exceed 1000 V and higher insulation test voltages are needed.

The MIT2500 offers both fixed range voltages of 50 V, 100V, 250 V, 500 V, 1000 V and 2500 V, as well as a variable range that allows any voltage between 50 V and 2500 V to be “dialed in”. This is supported by the new test voltage feedback control, which maintains the output test voltage to within 2% of the selected range, even when under test.

The MIT2500 uses the redesigned case, back-stand, and 6 cell battery compartment, as well as incorporating a guard terminal to reduce surface tracking currents that reduce accuracy at higher voltages.

All instruments are over-moulded for increased protection and achieve an IP54 weatherproof rating

INSULATION RESISTANCE TESTING

The feedback controlled insulation test voltage is now accurate to +2% -0% compared to the original +20%, providing a more accurate test voltage without the risk of over-voltage damage to circuits.

A variable range allows the exact test voltage to be selected from 50 V to 999 V in 1 V steps, (1kV to 2.5 kV in 10 V steps) providing 1100 test voltage options.

FEATURES INCLUDE:

- **Test voltages (New)**
 - 50 V, 100 V, 250 V, 500 V, 1000 V and 2500 V.
- **Guard terminal**
 - Improved performance on higher insulation test ranges.
- **2.5 kV Silicone test leads (New)**
 - Purpose designed high 2.5 kV silicone test leads are included as well as standard 1000 V CAT III / 600 V CAT IV general purpose test leads.
- **Variable test voltage (New)**
 - Adjustable test voltage from 50 V to 999 V in 1 V steps, 1000 V to 2500 V in 10 V steps.
- **2% test voltage accuracy**
 - The output test voltage is maintained within the tolerance or -0% +2% +2 V.
- **Stabilized test voltage**
 - The voltage is feedback controlled to ensure it remains within specification throughout the full test range.
- **Test voltage display (New)**
 - The actual test voltage is displayed on the smaller digital readout, with the measurement on the larger digital display.
- **Measurement range displayed (New)**
 - The test range is displayed during selection.
- **Measurement voltage display**
 - The measurement voltage is displayed during the test.

■ Analog arc

- The display also features an analogue arc to replicate the response of a moving coil display.

■ PI and DAR

- Automatic Polarization Index (PI) and Dielectric Absorption Ratio (DAR) functions. Polarization Index (PI): 10 min / 1 minute ratio
Dielectric Absorption Ratio (DAR): 60 sec / 30 sec ratio.

■ Timed testing

- Automatically test to a time limit.

■ 200 GΩ range

- Insulation testing up to 200 GΩ at ≥1000 V.

■ Test inhibit

- Prevents testing if voltages in excess of 25, 30, 50, 75 or 100 V (set by the user) are detected when making insulation tests. Default is 50 V.

■ Insulation buzzer

- The buzzer can be set to buzz if the insulation resistance is above a user adjustable limit, set in the Setup menu.

■ Test Lock

- Holds insulation test on continuously.

Test ranges extend from 10 GΩ to 200 GΩ depending on test voltage as below:

■ 50 Volts	10 GΩ
■ 100 Volts	20 GΩ
■ 250 Volts	50 GΩ
■ 500 Volts	100 GΩ
■ 100 Volts	200 GΩ
■ 2500 Volts	200 GΩ

The MIT2500 also includes a guard terminal to prevent errors from stray leakage paths.

VARIABLE INSULATION VOLTAGE (NEW)*

The variable mode provides a unique solution for awkward insulation voltage measurement applications. The range option allows an insulation test voltage from 50 V to 999 V in 1 V steps, 1.0 KV to 2.5 KV in 10 V steps.

TYPICAL APPLICATIONS INCLUDE

- Commercial Avionics
- Military Land, Marine and Air communications
- Manufacturing/production line goods
- Electrostatic measurement
- Component testing
- Battery powered traction and lifting equipment

GUARD TERMINAL

The guard terminal (G) is a third terminal on the connection panel. Connection of the guard terminal on certain applications provides a return path for parallel leakage currents that could otherwise create significant errors in the insulation measurement. This is especially so for surface contamination of equipment or cables.

- For voltages of 1000 V and above, or expected insulation values over 100 MΩ the guard terminal should be considered to reduce measurement error.

CONTINUITY (RESISTANCE) TESTING

■ Single resistance range (New)

- One range fully automatic from 0.01 Ω to 1.0 MΩ.

■ Auto test current selection

- Automatically uses the preferred test current for the load resistance under test.

■ Bi-directional testing (New)

- Option for automatic bi-directional testing without reconnecting leads.

■ Fast response time (New)

- Response time on contact buzzer has been reduced

■ 200 mA or 20 mA

- Either 200 mA or 20 mA continuity test currents are available. 20 mA test current will considerably increase battery life.

■ Lead null

- Lead resistance compensation (NULL) operates up to 10 Ωs of resistance.

■ Buzzer

- ON/OFF selected by simple push button.

■ Buzzer limit

- Continuity buzzer limit alarm provides adjustment of the maximum resistance the continuity buzzer sounds. This is adjustable from 1 Ω to 200 Ω in 12 steps.

■ Differential measurement (New)

- Allows the difference between two consecutive continuity tests to be measured

VOLTAGE MEASUREMENT

True RMS voltage measurement to 600 V ac or dc with resolution from 0.1 mV.

- Digital voltage measurement up to 600 V ac/dc
- Automatic display of frequency during voltage measurement.

DISPLAY

The display offers a combination of analog arc and a dual digital readout:

Analog arc:

- Full display width analog arc.
- Analog arc display shows essential charge and discharge characteristics not visible on a digital display.
- Single pointer "needle" response is similar to a moving coil meter. Setup functions allow control of Buzzer limit alarms, Continuity test currents, kΩ/MΩ/GΩ.

Dual digital display

- Large main digital readout for good visibility of all main measurement results
- Second digital display for additional data such as:
 - Insulation test voltage.
 - Insulation leakage current.
 - Supply frequency (when measuring volts).
 - Test mode eg. PI, DAR or t (t = Timer mode)

OTHER FUNCTIONS AND FEATURES

Setup functions:

Allow control of:

- Continuity buzzer limit alarms,
- Insulation buzzer limit alarms,
- Insulation LOCK
- Insulation test timer duration
- Backlight ON duration
- Sleep timer
- Continuity test currents,
- Factory reset

Weatherproof - Every tester is sealed to IP54, providing a weatherproof case to reduce the chances of water ingress, including the battery and fuse compartment.

Tough housing - Rubber over moulding combines the tough shock absorbing outer protection with excellent grip, on a strong modified ABS housing, providing an almost indestructible case.

Batteries - Battery requirements are 6 AA batteries of either standard Alkaline or Nickel Metal Hydride (NiMH) rechargeable type, providing a minimum of 3000 insulation tests at 1000 V.

The MIT2500 is enabled to internal charging when used with the optional charging pack.

STORAGE AND DOWNLOADING RESULTS

Revised Bluetooth® and pairing procedures have made the MIT2500 far easier to pair and download data. The test results are downloaded to a CSV file which can then be opened as an Excel® spreadsheet.

SAFETY

Designed to be exceptionally safe to use, fast detecting circuitry prevents damage to the instruments if accidentally connected to live circuits or across phases. Specifically, all instruments:

- Meet the international requirements of IEC61010 and EN61557.
- Live circuit detection inhibits insulation testing on circuits above 25, 30, 50, 75 or 100 V default (50 V).
- Live circuit detection and test inhibit on continuity measurements.
- Default display of live circuit voltage on all ranges.
- Detection and inhibit functions even if the protection fuse has failed.
- Suitable for use on CAT IV applications and supply voltages to 600 V.

FEATURES AND BENEFITS

- Designed for the Telecommunications and Cable TV markets
- Insulation testing up to 500 V and 100 GΩ range in a hand held instrument
- 3 wire connection for Tip, Ring and Earth connection (New)
- Gated access to 500 V to prevent accidental damage (New)
- Adjustable insulation test voltage from 10 V to 500 V (New)*
- Differential measurement capability (New)
- New case design with optional magnetic hanging strap (New)
- Rechargeable options for mains and car charging (New)
- Single range, faster continuity testing from 0.01 Ω to 1 MΩ (New)

MIT2500 INCLUDED ACCESSORIES:

Silicone test leads:

2.5 kV rated test leads fitted with medium size Croc clips

1 x Red, 1 x Black, 1 x Blue (Guard)

1 kV rated standard test leads with Probes and clips

1 x Red, 1 x Black

OPTIONAL ACCESSORIES

Battery charger:

A charging pack is available to charge the MIT2500 when fitted with NiMH AA batteries.

Remote switch probe

APPLICATIONS

- Single and three phase rotating machinery
- Single and multi-core cable testing
- Motor testing

FEATURES

- Designed for the Electrical and Industrial markets
- Insulation testing up to 2.5 kV (New) and 200 GΩ range in a hand held instrument
- Guard terminal for high resistance accuracy (New)
- Adjustable insulation test voltage from 50 V to 2500 V (New)
- Stabilized insulation test voltage (New)
- Rechargeable options for mains and car charging (New)
- Single range, faster continuity testing from 0.01 Ω to 1 MΩ (New)
- Polarization Index (PI) & Dielectric Absorption Ratio (DAR)
- 600 V Trms AC and DC voltage measurement
- New case design with optional magnetic hanging strap (New)
- Test result storage and review and Bluetooth® download
- Live circuit detection and protection
- CAT IV 600 V applications
- IP54

FUNCTIONAL SUMMARY

INSULATION RANGES	
50 V / 100 V / 250 V / 500 V	■
250 V 500 V / 1000 V	■
2500 V	■
VARIABLE voltage from 50 V to 2500 V	■
PI / DAR / timed	■
Lock button on MΩ	■
Guard terminal	■
CONTINUITY	
Continuity 0.01 Ω - 1 MΩ	■
Auto reverse polarity (setup ON-OFF)	■
Lead null (<10 Ω)	■
VOLTAGE	
AC/DC Volts 600 V	■
mV AC/DC range	■
Frequency measurement 15-400 Hz	■
Input impedance	250 kΩ
CAPACITANCE	
Capacitance 0.1 nF - 10 μF	■
OTHER FEATURES	
PASS/FAIL on limit alarms	■
Auto power down (setup)	■
On-board memory	■
Bluetooth® and software	■
Recharger ready	■
AA alkaline or NiMH	■
CAT IV/600 V	■
ACCESSORIES	
Silicone leads (Red, Black, Blue with probes and clips)	■
2.5 kV silicone croc clip leads	■
OPTIONAL switched probe available	■
OPTIONAL battery charger available	■

SPECIFICATIONS

All quoted accuracies are at +20 °C

Insulation.

Insulation accuracy

50 Volts	10 GΩ	± 2%	± 2 digits ± 4.0% per GΩ
100 Volts	20 GΩ	± 2%	± 2 digits ± 2.0% per GΩ
250 Volts	50 GΩ	± 2%	± 2 digits ± 0.8% per GΩ
500 Volts	100 GΩ	± 2%	± 2 digits ± 0.4% per GΩ
1000 Volts	200 GΩ	± 2%	± 2 digits ± 0.2% per GΩ
2500 Volts	200 GΩ	± 2%	± 2 digits ± 0.2% per GΩ

Service Error: BS EN 61557-2 (2007).

50V	± 2.0% ± 2d, 100kΩ - 900kΩ	± 10.5%
100V	± 2.0% ± 2d, 100kΩ - 900kΩ	± 10.3%
250V	± 2.0% ± 2d, 100kΩ - 900kΩ	± 10.3%
500V	± 2.0% ± 2d, 100kΩ - 900kΩ	± 10.3%
1000 V	± 2.0% ± 2d, 100kΩ - 900kΩ	± 11.5%

Guard terminal performance

<5% error at 500 kΩ parallel circuit resistance with 100 MΩ load

Display range

Analog: 1 GΩ full scale

Resolution

0.1 kΩ

Short circuit/charge current

2 mA +0% -50% to EN61557-2 (2007) [except 2500 V]

Terminal voltage accuracy

-0% +2% ± 2 V

Test current

1 mA at min. pass value of insulation to a maximum of 2 mA max EN61557 : 0.10 MΩ to 1.0 GΩ

Operation

Leakage current display Voltage

10% ±3 digits

±3 ±2 digits ±0.5% of rated voltage

Timer control

Countdown timer 60 second (adjustable to 10 minutes)

NOTE

Above specifications only apply when high quality silicone leads are being used.

Continuity

Continuity range

0.01 Ω to 1.0 MΩ (0 to 1000 kΩ on analog scale)

Continuity accuracy

± 3% ± 2 digits (0 to 100 Ω)
±5% ±2 digits (>100 Ω- 500 kΩ)
Service Error: BS EN 61557-4 (2007) - ± 2.0%, 0.1Ω - 2Ω ± 6.8%

Open circuit voltage

5 V ± 1 V

Polarity

Single polarity (default) / dual polarity (configurable on setup)

Test current

200 mA (-0 mA +20 mA) (0.01 Ω to 4 Ω)

Lead resistance

Null up to 10 Ω

Voltage

Voltage range	AC: 10 mV to 600 V TRMS sinusoidal (15 Hz to 400 Hz) DC: 0 to 600 V Unspecified: 0 - 10 mV (150 to 400 Hz)
Volt range accuracy	AC: $\pm 2\% \pm 2$ digits DC: $\pm 2\% \pm 2$ digits Service Error: BS EN 61557-1 (2007) - $\pm 2.0\% \pm 2d$, 0V - 300Vac/dc ± 5.1
Waveform	Non-sinusoidal waveforms: $\pm 3\% \pm 2$ digits >100 mV to 600 V TRMS $\pm 8\% \pm 2$ digits 10 mV to 100 mV TRMS
Default voltmeter	$\pm 0.5\% \pm 1$ digit (100 Hz to 400 Hz) unspecified

Frequency

Frequency measurement range	15 Hz - 400 Hz
Frequency measurement accuracy	$\pm 0.5\% \pm 1$ digit
Capacitance measurement	
Capacitance range	0.1 nF to 10 μ F
Capacitance accuracy	$\pm 5.0\% \pm 2$ digits (1 nF-10 μ F)

Result storage

Storage capacity	>1000 test results
Data download	Bluetooth® wireless Bluetooth® Class II
Range	Up to 10 m (33 ft)

Power supply

6 x 1.5 V cells type IEC LR6 (AA, MN1500, HP7, AM3 R6HP)
Alkaline
6 x 1.2 V NiMH rechargeable cells may be used.

Battery life

3000 insulation tests with duty cycle of 5 sec ON /55 sec OFF @ 500 V into 1000 k Ω
Charger (Optional): 12-15 V dc (accessory interface)

Dimensions

9.00 in x 4.25 in x 2.32 in
(2.28 mm x 108 mm x 63 mm)

Weight

1.8 lb (815 g)

Weight (instrument and case)

3.86 lb (1.75 kg)

Fuse

Use only 2 x 500 mA (FF) 1000 V 32 x 6 mm ceramic fuse of high breaking capacity HBC 30 kA minimum. Glass fuses **MUST NOT** be fitted.

Safety protection

The instruments meet EN 61010-1 (1995) to 600V phase to earth, Category IV. Refer to safety warnings supplied.

EMC

In accordance with IEC61326 including amendment No. 1.

Temperature coefficient

<0,1% per °C up to 1 G Ω
<0,1% per °C per G Ω
above 1 G Ω

Environmental

Operating temperature	14° F to 131° F (-10° C to +55° C)
Humidity	90% RH at 40 °C
Storage temperature	-13° F to +158° F (-25° C to +70° C)
Calibration temperature	-8° F (+20° C)
Maximum altitude	6560 ft (2000 m)
IP rating	IP54

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc and is used under license.

ORDERING INFORMATION

Description	Order Code	Description	Order Code
MIT2500 - 50 V to 2.5 kV testings with guard, result storage, recall and downloading of results	1006-764		
Included accessories		Optional accessories	
Red/Black/Blue 1 kV silicone test leads with probes and clips	1007-781	Replacement Red/Black/Blue 1 kV silicone test leads with probes and clips	1007-781
Red/Black/Blue 2.50 kV silicone test leads with clips	1007-637	Red/Black/Blue 2.50 kV silicone test leads with clips	1007-637
Owners Information CD	download at www.megger.com	AC charger kit	1007-464
Batteries 6 x AA Alkaline	1002-753	12 V DC battery charger (requires AC charger kit)	1004-183
Hard carry case	2006-649	SP5 Switched probe	1007-157
Download manager software	download at www.megger.com	Test lead set and crocodile clips	1002-001
		2 wire 500 mA fused test lead set	1002-015
		Batteries (6 x NiMH)	1002-753

SALES OFFICE
Megger
2621 Van Buren Avenue
Norristown, PA 19403 USA
T 610 676 8500
E VFCustomerSupport@megger.com

MIT2500_DS_US_V01 download
www.megger.com
ISO 9001
The word 'Megger' is a registered trademark