



1370 West Main St.
Salem, IL 62881
Phone: 618-548-3555
Fax: 618-548-3557
Email: sales@bettendorfstanford.com
Web: www.Bettendorfstanford.com

BSI 55 Scoop Bagger

BSI 55 Scoop Bagger Details

SPECIFICATIONS:

Maximum Loaf Size:

Length 16" (406 mm), width 5 1/2" (140 mm), height 6" (152 mm)

Electrical Requirements:

230/460 volts, 60 Hz, 3-phase AC 15 amp service for 2hp drive motor.

Closer unit requirements are additional depending upon the unit.

Other voltages available on request.

Rated speed:

Variable speed up to 70 loaves per minute recommended speed of 50

Air requirements:

12 CFM (340 cm) of free air at 80 PSI (5.625 kg/cm).

Weight (Approximate):

1650 lbs. net (750 kg), 1850 lbs. shipping (840 kg), 2650 lbs. export (1205 kg)

STANDARD FEATURES:

- 2hp motor
- Plant 3 Phase voltage with DC control voltage
- NEMA 4 enclosures with sealtite conduit
- AB PLC with 6" HMI
- Nexen clutch/brake
- Conveyor dead plates are spring loaded
- Infeed conveyor with phase adjuster
- Shuttle assembly w/composite bushings
- Roller blockade assembly
- Double wicket holder
- Aluminum guarding
- 30:1 cone drive gearbox
- 6' extended discharge
- Air craft grade rod ends
- Self lubricated chains

ACCESSORIES:

- Additional conveyor lengths available
- Upper and lower scoops included
- New drive cam for smoother product delivery
- Bag tensioner device
- Slicer hook up

OPTIONS:

- Automatic double wicket
- Arch flash detection
- Left hand frame configuration
- Right hand frame configuration (shown below)

TECHNICAL LAYOUT:

